

FOILBOARD® INSULATION SYSTEMS INSTALLATION GUIDE

To achieve maximum thermal performance and to ensure a fast and simple installation of Foilboard® GREEN rigid insulation panel to a shed/garage wall and/or roof, Foilboard Australia recommends the following method.

What do you need?


- Use Foilboard® Ultra Fasteners for GREEN 20 and GREEN 25 (Use Timber or Steel fasteners depending on application)



Foilboard® Silver Joining tape

Foilboard® Spacer Blocks (Optional)

How to Install?



- ✓ Foilboard® Panels don't need to join on a batten or purlin. Butt join and tape to ensure continuous insulation.
- ✓ Install Foilboard® silver side as the finish to brighten your shed or garage space.
- ✓ Place the fastener 50mm in from the edge of the insulation panel to leave room for the tape.
- ✓ Off cuts can be used as a spacer block to help minimise wastage
- ✓ Foilboard should not be installed under skylight/laser light or glass sheeting

TOP TIPS



***Please note that Foilboard should not be installed to the underside of 'skylight roof/laser light/glass sheeting' due to the extreme temperatures that will be created from the trapped air space between the sheeting and Foilboard. Alternatively, you could replace the skylight/laser light sheets or paint them prior to installing Foilboard.**

SHED / GARAGE



INFORMATION HOTLINE: 1800 354 717

It's the smarter way to insulate

www.foilboard.com.au